

LFS LOFOT

LED FLOODLIGHT
LED LICHTFLUTER

MATERIAL ► stop aluminium, szkło hartowane
MATERIAL ► aluminum alloy, tempered glass
MATERIAL ► aluminiumlegierung, gehärtetes glas

- 230V
50Hz
- DF
≥ 0.9
- 4000K
6000K
- CRI
≥ 70
- 120°
- IK08
- 25000h
L70B50
- +35°C
-15°C
- IP65
-






LFS-050



LFS-200

[mm]	a	b	c	d
LFS-010:	111	122	25	103
LFS-020:	161	168	28	133
LFS-030:	202	213	30	165
LFS-050:	242	255	32	195
LFS-100:	318	332	58	271
LFS-150:	361	378	59	290
LFS-200:	402	415	66	330



wbudowane diody LED



radiator odprowadzający ciepło



dławnica z przewodem zasilającym



uchwyt montażowy



wytrzymałe szkło hartowane



kod	EAN	opakowanie	barwa światła [K]	moc [W]	strumień świetlny [lm]	klasa energetyczna
C65-LFS-010BL-4K	5900280946867	1/50	4000	10	1000	E
C65-LFS-010BL-6K	5900280919892	1/50	6000	10	1020	E
C65-LFS-020BL-4K	5900280946874	1/20	4000	20	2000	E
C65-LFS-020BL-6K	5900280919908	1/20	6000	20	2050	E
C65-LFS-030BL-4K	5900280946881	1/20	4000	30	3000	E
C65-LFS-030BL-6K	5900280919915	1/20	6000	30	3100	E
C65-LFS-050BL-4K	5900280946898	1/10	4000	50	5000	E
C65-LFS-050BL-6K	5900280919922	1/10	6000	50	5150	E
C65-LFS-100BL-4K	5900280946904	1/5	4000	100	10 000	E
C65-LFS-100BL-6K	5900280924254	1/5	6000	100	10 300	E
C65-LFS-150BL-4K	5900280946911	1/5	4000	150	15 000	E
C65-LFS-150BL-6K	5900280924261	1/5	6000	150	15 500	E
C65-LFS-200BL-4K	5900280946928	1/5	4000	200	20 000	E
C65-LFS-200BL-6K	5900280924278	1/5	6000	200	21 000	E