

Parametry podstawowe

Valve product range	SpaceLogic
Typ produktu lub komponentu	Valve
Valve type	Pressure independent
Valve product series	VP222F
Zastosowanie urządzenia	Air handling unit Fan coil unit Radiation panel Terminal unit
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Flanged
Body size	250 mm (10 in)
Pipe size	250 mm
Flow characteristic	Linear
Pressure allowable static	16 bar
Pressure class	PN16
Operating fluid temperature	-10...120 °C
Pressure fluid max delta P normal life	399,90 kPa
Flow rate minimum (gpm)	528 gal(US)/min
Flow rate nominal (gpm)	1320 gal(US)/min
Flow rate maximum (gpm)	1452 gal(US)/min
Flow rate minimum (lps)	31 l/s
Flow rate nominal (lps)	83 l/s
Flow rate nominal (m³/h)	300 m³/h
Flow rate maximum (lps)	92 l/s
Flow rate minimum (m³/h)	112 m³/h
Flow rate maximum (m³/h)	330 m³/h
Pressure differential minimum (kPa)	45 kPa
Pressure differential maximum (kPa)	600 kPa
Pressure differential minimum (psi)	6.53 psi 6.53 psi
Pressure differential maximum (psi)	87 psi 87 psi
Control valve rangeability	1000:1
Stroke length	30 mm
Seat leakage	Port A: 0.01% of Qnom
Accuracy setting knob	5 %
Stem movement	Linear
Materiał korpusu	Grey cast iron GG-25
Seat material	Port A: stainless steel AISI 420
Stem material	Stainless steel
Stem seal material	EPDM (ethylene propylene diene monomer)

Material diaphragm	EPDM (ethylene propylene diene monomer)
Kraj docelowy	Europe Asia Pacific. Australia.



Parametry uzupełniające

Flow rate maximum (lph)	330000 l/h
Flow rate minimum (lph)	112000 l/h
Flow rate nominal (lph)	300000 l/h

Jednostka opakowania

Jednostka miary opakowania 1	PCE
Ilość jednostek w opakowaniu 1	1
Wysokość opakowania 1	73,0 cm
Szerokość opakowania 1	97,0 cm
Długość opakowania 1	73,0 cm
Waga opakowania 1	342,0 kg

Oferta zrównoważonego rozwoju

Europejska dyrektywa RoHS	Zgodność z pro-active (produkt poza zakresem obowiązywania dyrektywy UE RoHS)
Bez rtęci	Tak
Norma RoHS Chiny	 Dyrektywa RoHS Chiny
Informacje na temat zwolnienia z RoHS	 Tak

Warunki gwarancji

Gwarancja	18 miesięcy
-----------	-------------