

Parametry podstawowe

Typ produktu lub komponentu	Valve
Valve type	Globe
Valve product series	V321
Valve model	V321/80/100
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	Flanged
Valve connection size	DN80 (ISO 7005-2)
Pipe size	80 mm
Body size	80 mm (3 in)
Flow characteristic	Equal percentage
Flow coefficient	92.5 cv 80 kvs
Pressure class	PN16
Operating fluid temperature	-10...130 °C
Pressure fluid max delta P normal life	82,74 kPa
Control valve rangeability	Greater than 30:1
Stroke length	30 mm
Seat leakage	Port A: Less than 0.05 % of kvs
Stem flow action	Stem up closes A and opens B to AB
Stem movement	Linear
Trim material	Stainless steel
Materiał korpusu	Grey cast iron GG-25
Seat material	Port A: stainless steel AISI 420 Port B: stainless steel AISI 420
Stem material	Stainless steel 316Ti
Plug material	Stainless steel AISI 420
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A: metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Kraj docelowy	Europe Asia Pacific. Australia.

Jednostka opakowania

Jednostka miary opakowania 1	PCE
Ilość jednostek w opakowaniu 1	1
Wysokość opakowania 1	20,0 cm
Szerokość opakowania 1	32,0 cm
Długość opakowania 1	34,5 cm
Waga opakowania 1	22,35 kg

Warunki gwarancji

Gwarancja

18 miesięcy
