



Parametry podstawowe

| | |
|--|--|
| Typ produktu lub komponentu | Valve |
| Valve type | Globe |
| Valve product series | V222 |
| Valve model | V222/65/63 |
| Medium compatibility | Glycol 25 % Glycol 30 % Glycol 50 % Water |
| Valve configuration | 2-Way |
| Valve connection type | Flanged |
| Valve connection size | DN65 (ISO 7005-2) |
| Pipe size | 65 mm |
| Body size | 65 mm (2-1/2 in) |
| Flow characteristic | Equal percentage |
| Flow coefficient | 72.84 cv 63 kvs |
| Pressure class | PN16 |
| Operating fluid temperature | -10...150 °C |
| Pressure fluid max delta P normal life | 799,79 kPa |
| Control valve rangeability | Greater than 50:1 |
| Stroke length | 30 mm |
| Seat leakage | Port A: Less than 0.05 % of kvs |
| Stem flow action | Stem down closed |
| Stem movement | Linear |
| Trim material | Stainless steel |
| Materiał korpusu | Grey cast iron GG-25 |
| Seat material | Port A: stainless steel AISI 420 |
| Stem material | Stainless steel AISI 420 |
| Plug material | Stainless steel AISI 420 |
| Stem seal material | PTFE (polytetrafluoroethylene) |
| Seating seal material | Port A: metal to metal |
| Packing material | Spring-loaded PTFE v-ring |
| Kraj docelowy | Europe Asia Pacific. Australia. |

Jednostka opakowania

| | |
|--------------------------------|---------|
| Jednostka miary opakowania 1 | PCE |
| Ilość jednostek w opakowaniu 1 | 1 |
| Wysokość opakowania 1 | 18,5 cm |
| Szerokość opakowania 1 | 29,5 cm |
| Długość opakowania 1 | 35 cm |
| Waga opakowania 1 | 17 g |

Warunki gwarancji

Gwarancja

18 miesięcy
