



### Parametry podstawowe

Typ produktu lub komponentu	Valve
Valve type	Globe
Valve product series	V292
Valve model	V292/65/63
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Flanged
Valve connection size	DN65 (ISO 7005-2)
Pipe size	65 mm
Body size	65 mm (2-1/2 in)
Flow characteristic	Equal percentage
Flow coefficient	72.84 cv 63 kvs
Pressure class	PN25
Operating fluid temperature	-10...150 °C
Pressure fluid max delta P normal life	799,79 kPa
Control valve rangeability	Greater than 50:1
Stroke length	30 mm
Seat leakage	Port A: Less than 0.05 % of kvs
Stem flow action	Stem down closed
Stem movement	Linear
Trim material	Stainless steel
Materiał korpusu	Nodular cast iron EN-JS 1025
Seat material	Port A: stainless steel AISI 420
Stem material	Stainless steel AISI 420
Plug material	Stainless steel AISI 420
Stem seal material	PTFE (polytetrafluoroethylene)
Seating seal material	Port A: metal to metal
Packing material	PTFE (polytetrafluoroethylene)
Kraj docelowy	Europe Asia Pacific. Australia.

### Jednostka opakowania

Jednostka miary opakowania 1	PCE
Ilość jednostek w opakowaniu 1	1
Wysokość opakowania 1	18,5 cm
Szerokość opakowania 1	29,0 cm
Długość opakowania 1	33,5 cm
Waga opakowania 1	16,85 kg

## Warunki gwarancji

---

Gwarancja

18 miesięcy

---