



Power	30/40/50 W	Voltage	230 V
Luminous flux*	8750 lm (360°)	Colour temperature	3000/4000/6000 K
Light colour	CCT	Beam angle	120 °
IK	08	Protection class	IP65



 User manual

Technical data:

Product code	SLI047007_PW
Power	30/40/50 W
Nominal current	215 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.98
Useful luminous flux*	8750 lm (360°)
Luminous flux**	4650/6200/7750 lm (360°)
Light efficiency	175 lm/W
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PC/PC
IK	08
Protection class	IP65
Colour	White
Dimension (axbxc)	1500x86x70 mm
Weight	1.203 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux